







Designed for wall-mounted displays with exceptionally bright, uniform **LED** illumination

Enhance any indoor environment with the VF65 lightbox from Leach. A stunning addition to any retail space, exhibition stand or visitor attraction, the VF65 is a versatile and durable display that's sure to capture the attention of your audience. Season after season, event after event or campaign after campaign, the unit's printed graphics can simply be switched out to suit, reducing costs and minimising the environmental impact of keeping your visuals up to date. What's more, you can customise your lightbox with a range of lighting controls, colour temperatures, frame finishes and accessories for a unique, show-stopping display solution.

Frame							Applications				Illumination		
Depth (mm)	Min. Size (m)	Max. Size (m)	Fabric Graphic	Rigid Graphic	Curved Shapes	Double-Sided	Wall-Mounted	Column Wrap	Suspended	Freestanding	Acrylic Lightsheet	Beam LEDs to Edge	LED Strip Backboard
65	0.4 × 0.4	5 × 3	•	0	•	0	•	•	•	0	_	0	•

Suitable For:

- Wall-mounted displays (both illuminated and non-illuminated)
- Displays with rounded corners, arched or circular flat shapes using a radius down to 350mm
- 3D displays such as column wraps using a 90-degree corner joint and vertical profile

Quick specifications

● Standard ○ Available, please enquire — Not available



























- Illuminated VF65 lightboxes use a composite aluminium panel backboard with 6500K IP20 LED strips as standard
- Available in sizes from 0.4m x 0.4m to 5m x 3m to suit any space. Alternative sizes are available in the wider VF range
- Energy-efficient power consumption of 95W/M2 as standard
- Larger VF65 lightboxes can be supplied in sections for ease of transport and installation
- A choice of Internal or external power supplies
- Screw mounted to the wall through the rear of the panel for hidden fixings and improved aesthetics

Customisable Options


- Silver anodised finish as standard with the option to powder coat to any RAL colour
- Freestanding or suspended configurations can accept a non-illuminated fabric graphic to the reverse of the frame for dual-aspect branding potential
- Available with corner profiles to encompass columns and corners
- Display rigid graphic panels instead of fabric graphics with the addition of a VFT profile
- For warmer shades of illumination, LEDs are available in 5000K, 4000K and 3000K colour temperatures
- Cut running costs by specifying high-efficiency eco-LEDs which consume only half the power of standard LEDs with no compromise to brightness
- Various control options include remote-control dimmers, DMX or DALI controls, RGB colour changing, LED Pixel controls and Casambi controls
- Choose a retail-ready lightbox with the addition of our **Product Wall** shelving and accessories
- Swap out the composite aluminium panel backboard for a flexible backing sheet, ideal for flat pack transportation and installation in spaces with restricted access

Eco-friendly Credentials

- Manufactured from widely recycled aluminium
- The option of high-efficiency LEDs
- Built for a lifetime, the VF65 lightbox allows printed graphics to be updated without professional installation
- Lightbox frames and printed graphics are eligible for the Leach back-to-base recycling scheme*

Compatible Graphics

- We recommend that the VF65 is paired with our Eco-Screen tension fabric, which delivers a high-definition finish for printed graphics
- Discover our full range of graphic materials on our website weareleach.com





^{*}a chargeable service